

**PAT-NO:** JP360015189A  
**DOCUMENT-IDENTIFIER:** JP 60015189 A  
**TITLE:** BAKED PRINTING OF REINFORCED GLASS

**PUBN-DATE:** January 25, 1985

**INVENTOR-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
AOE, MASAHIRO	
UCHIUMI, HIDETA	

**ASSIGNEE-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
NAMIKI PRECISION JEWEL CO LTD	N/A

**APPL-NO:** JP58123883

**APPL-DATE:** July 7, 1983

**INT-CL (IPC):** B41M001/34 , G04B039/00

**US-CL-CURRENT:** 101/32 , 101/488

**ABSTRACT:**

**PURPOSE:** To perform a printing with a high quality efficiently on a glass of a wrist watch or the like without causing a difference in the baking adhesivity by baking a pattern on the reinforced glass arranged on a substrate high in the transmissivity for infrared rays with the irradiation of infrared rays.

**CONSTITUTION:** When a pattern 1 is formed on a reinforced glass 2 by screen printing and undergoes a baking treatment, the reinforced glass 2 is arranged on a substrate (e.g. Pyrex glass, transparent quartz plate)4 high in the transmissivity for infrared rays and infrared rays irradiates it from an infrared ray lamp 3 to bake the pattern 1.

EFFECT: There is no thermal effect on the reinforced glass body as the concentration of heat energy is possible on the pattern forming part. The use of the above- mentioned substrate allows the heating of the substrate by infrared rays passing through a part of the reinforced glass to prevent the lowering of the strength thereof otherwise caused by reverse transfer of heat to the glass.

COPYRIGHT: (C)1985,JPO&Japio